



Section	~b	~h	
mm			
mm			
AVX 10	10	8	
AVX 13	13	10	
AVP 13	13	10	

Orders as per length La.

AVX 10	
	La
mm	

710
713
735
750
763
800
813
825
875
913
925
937
940
944
950
965
975
990
1000
1013
1018

AVX 10

La

mm

1025
1045
1050
1075

1113
1125
1150
1155
1160
1175
1200
1225
1240
1250
1260
1275
1300
1340
1375
1385
1400
1450
1510
1515
1540
1550
1675
1735

AVX 13

La

mm

725
750
775
800
825
875
925
950
975
1000
1015

1018
1025
1050
1075
1100
1125
1175

AVX 13

La

mm

1200
1225
1250
1275
1300
1310
1325
1350
1375
1385
1400
1450
1460
1525
1550
1675
1750
2500

AVP 13

La

mm

865 *)
1525 *)
1750 *)

□ *) **Special version for KAROSA buses.**
Service free version with sections AVX10, AVX 13.
Belts are resistant to temperatures from -45 °C to +80 °C.
Increased resistance to mineral oils.
Increased resistance to abrasion.

Example of marking: □□ **AVX 10 -1000La SF**

AVX 10 - marking of section

1000 La - outside length

SF - marking of service free version